CE

ŞİŞECAM

Declaration of Performance
No: FRZ0600Z

TRC Helio Clear 6 mm

2006

Trakya Cam Sanayii A.Ş.
İş Kuleleri Kule 3 34330
4.Levent- İSTANBUL/TÜRKİYE
Tel: +90 212 350 50 50
www.trakyacam.com.tr/en/ce

EN 572-9:2006
Notified Test Body: 1750

Basic soda lime silicate float glass, intended to be used in buildings and construction works

Characteristics	AVCP System	Performance
Safety in the case of fire:		
Resistance to fire (13501-2)	1	NPD
Reaction to fire (13501-1)	3,4	A1
External fire behaviour (EN 13501-5)	3,4	NPD
Safety in use:		
Bullet resistance (EN 1063)	1	NPD
Explosion resistance (EN 13541)	1	NPD
Burglar resistance (EN 356)	3	NPD
Pendulum body impact resistance (EN 12600)	3	NPD
Resistance against sudden temperature changes and temperature differentials	4	40K
Wind, snow, permanent and imposed load resistance of the glass unit	4	6mm
Protection aganist noise:		
Direct airborne sound reduction (EN 12758)	4	31 (-2; -3) dB
Thermal properties:		
U-value (EN 673)	3	5,7 W/(m^{2}K)
Normal emissivity (EN 12898)	3	0,89
Radiation properties (EN 410):		
Light transmission	3	0,88
Light reflection outdoor	3	0,08
Light reflection indoor	3	0,08
Solar energy characteristics (EN 410):		
Solar transmission	3	0,78
Solar reflection outdoor	3	0,07
Solar reflection indoor	3	0,07

NPD: No performance determined

The performance of the product identified is in conformity with the declared performance above.
This declaration of performance is issued under the sole responsibility of the manufacturer.
Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Gökhan Atikkan Basic Glass Production Director	01 July 2013 İstanbul	